

Fields of application		
3	Liquids	Liquids (drops or sprays)
4	Large dust particles	Dust with a particle size > 5 µm
5	Gas particles and fine powder	Gases, vapours, sprays, smoke and dust with a particle size <5 µm
8	Short circuit electric arc	Short circuit electric arc in electrical devices
9	Molten metal and hot solids	Splashes of molten metal and the penetration of hot solids

Filters for welding protection			
Select the filter rating number as shown in the table below. The maximum deviation of the scale number is +/-1.			
Scale	Field of application	Gas	I/h
1,7	Assistant welder	-	-
3	Assistant welder	-	-
4	Braze welding	Acetylene	<70
	Oxy-fuel welding and cutting	Oxygen	<900
5	Braze welding	Acetylene	70:200
	Oxy-fuel welding and cutting	Oxygen	900:2000
6	Braze welding	Acetylene	200:800
	Oxy-fuel welding and cutting	Oxygen	2000:4000
7	Braze welding	Acetylene	>800
	Oxy-fuel welding and cutting	Oxygen	4000:8000

NOTE: For arc welding scale numbers from 8 to 14 are used depending on the type of electrode and current used. Ref. Tab.3 EN 169:2001.

Warning

Eye protection that is worn over standard ophthalmic spectacles may transmit impact from high speed particles thus creating a hazard to the wearer. Although every effort is made to ensure that materials that may come into contact with the skin of the wearer do not cause an allergic reaction, this may not happen for a minority of susceptible individuals, and if you are in this situation, you must stop wearing the eyewear immediately and seek professional advice.

Name of the manufacturer :

Scandia Gear Europe B.V.
Lorentzweg 31,
3208 LJ Spijkensse,
The Netherlands.

Certification body :

Certottica S.C.R.L. – Zona Industriale Villanova,
32013, Longarone (BL), Italy

Notified Body Number : 0530

Disclaimer

Scandia Gear is not liable for damages that result from the improper use of these products.



SCANDIA GEAR EUROPE B.V.
📍 Lorentzweg 31, 3208 LJ Spijkensse, The Netherlands
☎ +31 (0)181 600 955 📠 +31 (0)181 600 966
✉ info@scandiagear.com 🌐 www.scandiagear.com

SAFETY EYEWEAR



User's Instruction

www.scandiagear.com

ROTTERDAM SINGAPORE HOUSTON DUBAI

Since 1974
MARITIME OUTFITTERS

Scandia

SAFETY EYEWEAR

Thank you for choosing our safety eyewear

You have chosen a Scandia Gear Personal Protective Equipment. Please read these instructions prior to use and prior to any maintenance.

This multi-certified product belongs to Category II and is approved in accordance with the EU Regulation 2016/425 and the requirements of the European harmonized standard EN166:2001. This product has been subjected to an EU-type Examination performed by:

Certottica S.C.R.L. N.B. 0530
Zona Industriale Villanova,
32013, Longarone (BL), Italy

The PPE is designed so that, in foreseeable conditions of use, it can provide adequate protection to the user. The rating of the PPE is indicated by markings and related indexes on the frame and lenses. The rating is obtained from tests in which the prototypes were submitted.

The EU Declaration of Conformity (DOC) can be obtained through following link:
www.scandiegear.com

Note

Please ensure that the eyewear always fits well.

Model

The name of the model is always indicated on the barcode of the packaging.

Storage

Store in a dry place at room temperature and protect from sunlight. The eyewear must be transported and stored in the original package, at a temperature between 5°C and 30°C (41°F and 86°F) and a relative humidity of <80%.

Maintenance

The lenses must be cleaned regularly. This must be done using a mild detergent, at room temperature (20 ± 5°C). The anti-fog coated lenses should be

cleaned using a soft cloth under normal circumstances. The eyewear should provide adequate protection for a period exceeding 6 months and up to 2 years. Regularly check the status. Scratched lenses must be replaced or disposed of. The markings found on the lens and on the frame represent the ratings of the product and the appropriate field of application. Scandia Gear shall not be liable for damages arising from misuse and improper maintenance and preservation of the PPE itself.

Fitting of Spare Parts and Accessories

(if applicable): Use original spare parts only. To replace the lenses, first check the compatibility of the markings and mount the lenses in the correct position.

Lens markings

Scale number (only filters) – Identification of Manufacturer – Optical class – symbol of mechanical resistance – Field (s) of application (if applicable) – CE Marking.

Frame markings

Identification of the manufacturer – Applied standards – Field (s) of application (if applicable) – Mechanical resistance – CE Marking.

Scale number (filters only)		
Type of filter	Code number	Filter rating number
Filters for welding	None	1,2 : 16
Ultraviolet (UV) filters	2	1,5 : 5
Ultraviolet (UV) light filters with good color recognition	2C	1,2 : 5
Infra-red (IR) filters	4	1,2 : 10
Sun filter (the solar protection offered by the lens has no infra-red element)	5	1,1 : 4,1
Sun filter may (the solar protection offered by the lens has an infrared element)	6	1,1 : 4,1

NOTE : The filter code number is always followed by the filter rating number (both numbers are separated by a space), and together form the scale number.

Manufacturer's Identification	Scandia	Identification Of Scandia Gear Europe B.V.
-------------------------------	---------	--

Optical Class	
Code	Designation
1	On-going work
2	Intermittent work
3	Occasional work (not intended for prolonged use)

Mechanical resistance	
Code	Mechanical Strength Requirements
None	Minimum resistance specification
S	Increased resistance specification
F	Low energy impact
B	Medium energy impact
A	High energy impact

If the symbol F, B or A is not found on both the lenses and the frame, then the lower value is assigned to the complete set of safety glasses. If protection is required against high speed particles at extreme temperatures, then the safety glasses should be marked with the letter T immediately following the letter indicating the impact resistance, i.e. FT, BT, AT. If the letter indicating the impact resistance is not followed by the letter T, then the safety glasses should be used only against high speed particles at room temperature.

Performance of the lens	
Code	Designation
K	Abrasion resistance (to surface damage caused by fine particles)
N	Resistance to fogging
R	Resistance increased

Fields of application		
Code	Designation	Description of the field of application
None	Basic	Unspecified mechanical hazards and dangers from ultraviolet, visible, infrared and solar radiation